



Speed of opening, stability, descent rate

Inspection certificate number: **EP_308.2020**

Test Report

Manufacturer data

Manufacturer name: **Windtech Paragliders**
 Representative: **Gabriel Cañada**
 Street: **Francisco Rodriguez 7**
 Post code / Place: **33201 Gijon - Asturias**
 Country: **Spain**

Sample data

Name: **Windsos Drive Lite** Size: **M**
 Steerable ⁽¹⁾: **Yes** Maximum weight in flight ⁽²⁾ [kg]: **110**
 Weight ⁽³⁾ [kg]: **1.606** volume packed [cm³]: **4900**
 Serial number: **68107**

Test data ⁽⁴⁾

| | Test no. 1 | Test no. 2 |
|---------------|-------------------------|-------------------------|
| Place of test | Villeneuve | Villeneuve |
| Date of test | 20.05.2014 | 27.11.2020 |
| Inspector: | Claude Thurnheer | Claude Thurnheer |

Atmosphere AGL

| | Test no. 1 | Test no. 2 |
|------------|------------|--------------|
| [°C] | 18 | 4.3 |
| RH [%] | 68 | 74 |
| [hPa] | 962 | 977.3 |
| Wind [m/s] | 1 | 0.1 |

Summary of both results ⁽⁵⁾

| | EN | LTF |
|-------------------------------------|-----------------|-----------------|
| Time of opening test [s]: | 3.00 | 3.00 |
| Calculated descent rate test [m/s]: | 4.00 | 4.00 |
| Stability test: | POSITIVE | POSITIVE |
| Behaviour during descent test: | Stable | Stable |
| Glider ratio: | POSITIVE | |

If steerable:

| | | |
|--|-----------------|-----------------|
| Any flight procedure and/or configuration described in the user's manual | POSITIVE | POSITIVE |
|--|-----------------|-----------------|

Strength test - 40 m/s opening shock

Inspection certificate number: **EP_308.2020**

Test Report

Manufacturer data

Manufacturer name: **Windtech Paragliders**
 Representative: **Gabriel Cañada**
 Street: **Francisco Rodriguez 7**
 Post code / Place: **33201 Gijon - Asturias**
 Country: **Spain**

Sample data

Name: **Windsos Drive Lite** Size: **M**
 Steerable **Yes** Maximum weight [kg]: **115**
 Weight [kg] **1.606** volume packed [cm³]: **4900**
 Serial number: **900004**

Test data ⁽¹⁾

| | Test no. 1 | Test no. 2 |
|---------------------|---------------------|---------------------|
| Place of test | Illarsaz | Illarsaz |
| Date of test | 06.08.2014 | 06.08.2014 |
| Corrected mass [kg] | n/a | n/a |
| Inspector: | Alain Zoller | Alain Zoller |

Atmosphere AGL

| | Test no. 1 | Test no. 2 |
|------------|------------|------------|
| [°C] | n/a | n/a |
| RH [%] | n/a | n/a |
| [hPa] | n/a | n/a |
| Wind [m/s] | n/a | n/a |

Test results

| | Test no. 1 | Test no. 2 |
|---|-----------------|-----------------|
| Strength test (40m/s shock) | POSITIVE | POSITIVE |
| Aircraft speed uncertainty K=2 [m/s] ⁽²⁾ | 2.9 | 2.9 |

| Item / type no. | Validity | Manufacturer | S/N |
|-----------------|-----------------------|------------------|--------|
| Weight | check every 12 months | Air Turquoise SA | N/A |
| Geos n° 11 | 18.06.2025 | JDC elec. | Unit11 |
| Weak link | continuously | Tost | N/A |



Identification number: **MISC_168.2020**

Windtech Paragliders Windsos Drive Lite one size

Result summary

Inner container strength test. Applied minimum 700 N for at least 10 seconds and at maximum strength.

Duration at the required strength: **11.2 [s]**

The maximum strength before broken: **1688.3 [N]**

Place of declaration **Villeneuve**
Date of issue: **30.11.2020**
Managing director **Randi Eriksen**

Signature:

This signature approve the validity of the test report, and can be included in the inspection certificate 71.5.1

Air Turquoise SA has thoroughly tested the sample of riser/bridle mentioned above and certifies its conformity with the standards: **EN 12491: 2015 chapter 5.3.2 and LTF NfL 91/09 chapter 6.1.8**

| Instrument | Validity | Manufacturer | Type no. | S/N |
|---------------------|----------------------|-------------------|------------|---------|
| Load Cell (axial) | 04/09/2023 | Burster GmbH (DE) | 8431-10000 | 1185483 |
| Winch | check every 12 month | Arwin | 300/600 | N/A |
| Geos n° 11 Skywatch | 08/05/2020 | JDC elec. | Geos n° 11 | 22 |

⁽¹⁾ Inner container: container of the folded emergency parachute.

⁽²⁾ Inner container (the connection between handgrip and inner container) is loaded at min 700 [N] over 10 seconds. The deployment system is loaded until breaking. Each component is tested.

⁽³⁾ Calculated value include the value minus the uncertainty (on safe side) / The uncertainty stated is the expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor k = 2. The value of the measured lies within the assigned range of values with a probability of 95%.



Identification number: **MISC_170.2021**

Windtech Paragliders Windsos Drive Lite

Result summary

Maximum strength for riser, bridle **28319.8 [N]**

Place of declaration **Villeneuve**
Date of issue: **04.01.2021**
Managing director **Randi Eriksen**

Signature:

This signature approve the validity of the test report, and can be included in the inspection certificate 71.5.1

Air Turquoise SA has thoroughly tested the sample of emergency parachute mentioned above and certifies its conformity with the standards: LTF NfL II 91/09 chapter 6.1.4

| Instrument | Validity | Manufacturer | Type no. | S/N |
|---------------------|------------|--------------|--------------|----------|
| Load sensor | 04/09/2023 | HBM | 1-S9M/50KN-1 | 31314652 |
| Geos n° 11 Skywatch | 08/05/2020 | JDC elec. | Geos n° 11 | 22 |

⁽¹⁾ Riser: lowest part of the parachute system, which is connected to harness. Bridle: connection between riser and harness, can also be a strap.

⁽²⁾ The connecting strap has to have a minimum load capacity of 24000 [N]. The exposed part of the connecting belt has to be protected against environmental factors.

⁽³⁾ Calculated value include the value minus the uncertainty (on safe side) / The uncertainty stated is the expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor $k = 2$. The value of the measured lies within the assigned range of values with a probability of 95%.